AUGLAIZE COUNTY ENGINEERING BID FORM FOR BITUMINOUS MATERIAL

The Auglaize County Commissioners will be accepting sealed bids on Bituminous Material. Sealed bids can be mailed or hand delivered to Board of Commissioners, 209 South Blackhoof St., Room 201, Wapakoneta, OH 45895. Bids will be opened at 10:00 A.M. on Tuesday March 27, 2025 at said Commissioners Office. The Board of County Commissioners reserves the right to accept or reject any and/or all bids.

Bidder:	
Address:	
Phone:	
Email:	

We herewith submit a quotation, firm until December 31, 2025, to furnish the below listed materials in accordance with the attached bid specifications and requirements on the following page(s).

Authorized Representative Signature

Date

Asphalt Concrete

Item		Price per ton
ODOT 441, Type 1 Surface	At plant	
ODOT 441, Type 2 Intermediate	At plant	
ODOT 301, Base mix	At plant	
SS7 Cold Mix	At plant / Delivered	

Liquid Asphalt Emulsion

Item		<u>P</u>	rice per gallon
RS-2	Delivered		
RS-2P	Delivered		
HF RS-2P	Delivered		
Demurrage rate			per hour

Fog Seal

Item		Price p	er gallon	Recommended Application Rate (gal/ sq. yd.)
SS-1H (diluted 50%)	Delivered			
Alternate:	Delivered			
Demurrage rate	\$	per hour		

Past performance of supplier will be considered when Bituminous material is purchased by Auglaize County Engineer

Bituminous Material Bid Specifications

Material Testing:

The Auglaize County Engineer or his representative reserves the right to draw samples from all materials listed and supplied as a part of this bid document. The testing will be performed by an independent testing laboratory and all costs incurred shall be the responsibility of the Auglaize County Engineer. All samples will be taken at the project site and will be held for future reference and/or verification. The supplier may draw their own sample at the same time for comparison, but that sample shall be the responsibility of the supplier's representative.

Asphalt Concrete:

- All materials and mix designs shall be in accordance with Section 301 & Section 441, ODOT Construction and Materials Specifications dated January 1, 2023.
- A JMF shall be submitted for each mix design and plant location(s) quoted as a part of this bid document.

Liquid Asphalt Emulsion:

- Supply a technical data sheet showing the min/max test results for all products quoted as a part of this bid document. Standard tests shall be performed under specifications shown in AASHTO M316.
- The supplier shall provide the Auglaize County Engineer with QA/QC testing results in a timely manner for every 15,000 gallons of material supplied to Auglaize County.
- A comparison between the supplied technical data sheet, testing results performed by the Auglaize County Engineer as mentioned above and the supplier's QA/QC results will be the basis for acceptable materials. The Auglaize County Engineer reserves the right to reject substandard materials based on this comparison. Previous test results of a material and supplier will be considered when liquid asphalt emulsion is purchased.
- Demurrage will not begin for at least two (2) hours after arrival time. The demurrage rate thereafter shall be listed on the bid document.
- Some full loads of material may be billed directly to Townships at the order of the Auglaize County Engineer or his representative

Fog Seal:

- Supply a technical data sheet showing the min/max test results for all products quoted as a part of this bid document. Standard tests shall be performed under specifications shown in AASHTO M316.
- Residue by distillation, as tested per AASHTO T59, shall not be less than 30%.
- The supplier's recommended application rate shall be listed on the bid document as gallons per square yard.
- The supplier shall provide the Auglaize County Engineer with QA/QC testing results in a timely manner for every 15,000 gallons of material supplied to Auglaize County.
- A comparison between the supplied technical data sheet, testing results performed by the Auglaize County Engineer as mentioned above and the supplier's QA/QC results will be the basis for acceptable materials. The Auglaize County Engineer reserves the right to reject substandard materials based on this comparison. Previous test results of a material and supplier will be considered when fog seal is purchased.
- Demurrage will not begin for at least two (2) hours after arrival time. The demurrage rate thereafter shall be listed on the bid document.
- Some full loads of material may be billed directly to Townships at the order of the Auglaize County Engineer or his representative.